



Laundry Tower Single Unit Front Load 5.1 Cu. Ft. I.E.C Washer and 8 Cu. Ft. Electric Dryer

Laundry Tower

Available Products: ELTE730CAW

Available Colors: White

Version: 06/24

Product Specifications

Washer

Drum Material	Stainless Steel
Maximum Spin Speed	1100 RPM
Water Level Adjustment	Yes

Washer Options

Delay Start Time	1-12 Hours
Extended Refresh	Yes
Extra Rinse	Yes
Stain Treat	Yes

Washer Spin Speeds

Spin Speed Selections	4
Max	Yes
Medium	Yes
Low	Yes
No Spin	Yes

Temperature Settings

Eco Cold	Yes
Cool	Yes
Warm	Yes
Hot	Yes

Dispenser

Bleach Dispenser	Yes
Detergent Dispenser	Yes
Fabric Softener Dispenser	Yes
Prewash Detergent Dispenser	Yes

Dryer Cycles

Cycle Count	7
Allergen	Yes
Delicates	Yes
Séchage rapide	Yes
Heavy Duty	Yes
Normal	Yes
Timed Dry Time	Yes
Towels	Yes

Washer Cycles

Cycle Count	7
Clean Washer	Yes
Delicates	Yes
Fast Wash	Yes
Heavy Duty	Yes
Normal	Yes
Rinse and Spin	Yes
Towels	Yes

Soil Levels

Extra Light	Yes
Light	Yes
Normal	Yes
Heavy	Yes

Dryer

Balanced Dry	Yes
Drum Back Type	Painted Steel
Drum Material	Painted Steel
Dryness Level Selections	Yes
Lint Filter	Yes
Moisture Sensor	Yes

Dryer Options

Delay Start Time	1-12 Hours
Dry Boost	Yes
Extended Tumble	Yes
Wrinkle Release	Yes

Dryness Level

High	Yes
Normal	Yes
Low	Yes
Damp	Yes

Exterior

Door Latch	Yes
Reversible Door	Yes

Laundry Tower Single Unit Front Load 5.1 Cu. Ft. I.E.C	Laundry Tower
Washer and 8 Cu. Ft. Electric Dryer	
Available Products: ELTE730CAW	Available Colors: White
Version: 06/24	

Drying Temperatures

Low	Yes
Normal	Yes
High	Yes
Eco Dry	Yes

Controls

Cancel	Yes
Child Lock	Yes
Cycle Status Lights	Yes
Delay Start	Yes
Estimated Time Remaining	Yes
Control Lock	Yes
How to Cancel	Key Combination
Pause Function	Yes
Power On/Off	Yes
Start	Yes

Dimensions and Volume

Height	76 1/4"
Width	27"
Depth	32"
Minimum Depth for Installation	36"
Dryer Drum Capacity	8 Cu. Ft.
Dry Linen Capacity Tested Amount	11 kg

Energy Data

Energy Efficiency	Tier 1
kWh/year	50 kWh
Water Usage/Year	4154 Gallons

General Specifications

Chime On / Chime Off	Yes
Leveling Legs	Yes
Prop 65 Label	Yes
Warranty - Labor	1 Year
Warranty - Motor	10 Years
Warranty - Parts	1 Year
Warranty - Tub	Lifetime

Performance Certifications and Approvals

CEE Tier	Tier 1
ENERGY STAR Certified	Yes

Electrical Specifications

Minimum Circuit Required (Dryer)	30 Amps
Minimum Circuit Required (Washing Machine)	15 Amps
Voltage Rating (Dryer)	208/240v
Voltage Rating (Washing Machine)	120v

Installation


Dryer Power Cord Included	Yes
Washer Power Cord Included	Yes
Ventilation Type	Vented

Certifications and Approvals

ADA Compliant	No
---------------	----

Installation Diagram

Laundry Center Dimensions



¹ Dryer electrical supply on rear of unit.

 **NOTE**

- Allow minimum 36" of depth space for proper installation with 90° quick turn elbow for venting.
- Connection of water inlet hose on steam laundry center adds 3/4 in. (2 cm) to installation depth.
- Power supply cord length on washer approximately 60 inches (152.5 cm).
- Drain hose length on washer approximately 59 inches (150 cm).
- Power supply cord length on gas laundry center or electric Canadian laundry center approximately 60 inches (152.5 cm).

Laundry Center Dimensions	
1. Unit width	27" (69 cm)
2. Height to gas supply pipe on rear of gas unit	39.7" (101 cm)
3. Centerline height for rear vent	41.8" (106 cm)
4. Floor line	--
5. Unit height	76.3" (194 cm)
6. Door clearance	53.9" (137 cm)
7. Unit depth	31.9" (81 cm)
8. Width distance to water connections	7.8" (20 cm)
9. Height to water connections	35.7" (91 cm)
10. Height to washer power connections	35.5" (91 cm)
11. Width distance to washer power connections	7.1" (18 cm)
12. Height to dryer electrical supply	48" (122 cm)