

Nikolatesla Flux Scratch Proof


Specification sheet

Downdraft induction cooktop



Learn more

MEASUREMENTS



	ENF430AS	ENF436AS
A	30 5/16" (77.05 cm)	36" (91.54 cm)
B	22 9/16" (56.4 cm)	
C	10 3/16" (25.9 cm)	
D	2 9/16" (6.4 cm)	
E	6 13/16" (17.29 cm)	

DESCRIPTION

Discover the future of efficient and safe cooking with Nikolatesla Flux Scratch Proof. Induction technology that redefines your cooking experience. This sleek induction cooktop now features scratch proof glass with an integrated aspiration system equipped with a powerful central blower of 600 CFM, it can reach very high performance levels in terms of air capture, noise level, and energy efficiency. Perfect to compliment any kitchen design, Nikolatesla Flux Scratch Proof is available in 30" & 36" widths.



FEATURES

- Timer
- Child lock
- Pot self-detection
- Easy to maintain
- Stop and go
- Delay switch off
- CFM reduction system
- Temperature manager
- Long life filter ++
- Bridge zones
- Total integration
- Airmatic
- Touch controls



GENERAL PROPERTIES

Width	30"	36"
Model	ENF430AS	ENF436AS
Dimensions	30"W x 22 1/4"D x 10 3/16"H	36"W x 22 1/4"D x 10 3/16"H
Electrical	220V-60Hz, 7.7Kw, 34.5A	
Finish	Tempered, Ultra Deep Matte Black Ceramic Scratch Proof Glass	
Controls	Electronic glass touch & slide w/red illumination	
Installation type	Ducted out or recirculating w/kit	
Ventilation'	4 speed (3 speed + boost)	
Blower Type (Internal)	600 CFM	
Noise (Min-max sones)'	1.5-6.8 Sones	
Grease filter	4 layer, black anodized aluminum mesh grease filter	
Cooking zones	4 Cooking Zones (3.7 kW) - 7 1/2" x 7.9"	
Heating type	Induction	
Heating level	10 levels (9 + boost, see details in chart below)	

KITS

Recirculating	KIT0192385 (2 ceramic carbon filters)
---------------	---------------------------------------


WARRANTY:* Two (2) Years In-Home Labor. Earn an additional One (1) by registering on elica.com
Two (2) Years Parts. Earn an additional Three (3) by registering on elica.com

Cooking level	Power (W)
Level 1	63 W
Level 2	105 W
Level 3	168 W
Level 4	252 W
Level 5	378 W
Level 6	588 W
Level 7	882 W
Level 8	1344 W
Level 9	2100 W
Booster	3700 W

Glass specifications


Material	Glass ceramic cooking panel
Appearance	Matte-black color
Thickness	4 mm
Color in reflexion	Black
Color in transmission	Amber
Surface structure	Though crystal smooth scratch & stain-resistant

SELF RIMMING INSTALLATION



	ENF430AS	ENF436AS
a	28 3/4" (73.03 cm)	34 9/16" (87.7 cm)
b	21 1/8" (53.6 cm)	
c	2" (5 cm) min	
d	1 5/16" (5 cm)	

FLUSH MOUNTED INSTALLATION



	ENF430AS	ENF436AS
a	30 7/8" (77.35 cm)	36 1/8" (91.8 cm)
b	22" (56.76 cm)	
c	28 3/4" (73.03 cm)	34 9/16" (87.7 cm)
d	21 1/8" (53.65 cm)	
e	1 5/16" (5 cm) min	
f	4 x Ø7	
g	1/4" (0.63 cm)	



The product images shown are for illustration purposes only and may not be an exact representation of the product.

¹ CFM and Noise data indicate the performance of the hood blower tested according to international standards. For AHAM Certified Ratings, established in accordance with California Title 24 Standardized test procedure, please refer to AHAM Certified Product Directory. Electric Ratings are declared according to UL.

² For valid warranty extension, register within 3 months from purchase. For USA & Canada Users Only. Please review terms and conditions.